



CEMB[®] **USA**
WHEEL SERVICE EQUIPMENT

SM675

Professional grade articulating swing arm tire changer with leverless mount head and high-performance BPS (Bead Press System) is the perfect choice for all OEM automotive and light truck wheel including difficult to mount stiff side wall low-profile high performance tires, deep drop center rims and multi-ply commercial and industrial wheel applications. The unique design utilizes an extremely rigid column and vertical arm with pneumatic locking and high-quality locking roller guides for long lasting, smooth movement.



- Locking Roller Guides**
- Wheel Lift**
- Self-Centering Turntable**
- Leverless Mount Head**
- Side Shovel**
- Bead Pressing System**

STANDARD MANUAL ACCESSORIES

Bead Lifting Lever



Bead Lifting Lever Cover



Plastic Lever



Leverless Head Front Insert



Leverless Head Rear Insert



Clamp Cover



Centering Cone Extension



Centering Cones



Hand Free Clamp



Bead Breaker Cover



DIMENSIONS

Power Supply:	220V, 1ph, L6-20p
Air Pressure:	Manual
Max. Rim Diameter:	26" (661 mm)
Max. Rim Width:	15" (380 mm)
Max. Tire Diameter:	36" (915 mm)
Turn Table Speed:	8-15 rpm
Shipping Weight:	1050 lbs. (476 kg)



CEMB[®] **USA**
WHEEL SERVICE EQUIPMENT

678-717-1050

www.cemb-usa.com