



CEMB[®] U
S
A
WHEEL SERVICE EQUIPMENT

SM645HPA

A professional quality automatic locking tilt-column tire changer features HPA high performance press arm, additional drop center press arm and tire lift helper, highly recommended to easily aid in the servicing of high performance and run flat tires with stiff sidewalls and difficult wheels with deep drop centers. Features dual table clamping cylinders with Space-Saver under table adjustable clamping range.

Press Arm & Help Arm
Self-Centering Turntable
Automatic Tilt-back
Bead loosening system
Side Shovel
Two Stage Inflation



STANDARD MANUAL ACCESSORIES

Bead Lifting Lever



Bead Lifting Lever Cover



Rear Inserts



Front Inserts



Clamp Cover



Bead Breaker Cover



DIMENSIONS

Power Supply: 110V, 1ph
Air Pressure: 115-145 psi (8-10 bar)
Max. Rim Diameter: 26" (661 mm)
Max. Rim Width: 13" (380 mm)
Max. Tire Diameter: 44" (1118 mm)
Turn Table Speed: 8-15 rpm
Shipping Weight: 950 lbs. (431 kg)



CEMB[®] U
S
A
WHEEL SERVICE EQUIPMENT

678-717-1050

www.cemb-usa.com